



PRODUCT KEY BENEFITS

- HPL head board and foot board are easier to clean and to disinfect.
- HPL color can be customized according to the room interior.
- Back rest retraction to ensure patient's comfort and ergonomic position.
- Stainless side rail to minimize risk of falling, no entrapment zone, easy to clean and to disinfect.
- Hi-low function as low as 35 cm from ground level.
- Foldable crank with torque release system.
- Upgradeable to electric hospital bed.

SPECIFICATIONS OF HOSPITAL BED 3 CRANK - 0103

Overall Dimensions	: 2160 mm x 980 mm x 635 mm.
Construction	: Made of 30 mm x 60 mm and 30 mm x 30 mm steel pipe.
Crank Mechanism	: Ergonomic back rest design with retraction up to 110 mm and elevation up to 75°. Adjustable knee raise with elevation up to 35°. Adjustable high-low position with range of 620 mm - 350 mm without mattress.
Mattress Platform	: Made of steel sheet with hollow steel pipe safety frame.
Head & Foot Panel	: Made of High Pressure Laminate (HPL), detachable.
Safety Side Rail	: Made of stainless steel, collapsible. Automatic locking and unlocking system with one touch folding.
Castor	: Four 5" castors from Tente Germany, swivel 360°, two with brakes.
IV Stand	: Made of stainless steel pipe (with two hanger hooks), 6 optional locations.
Painting	: Powder coating.
Accessories	: Name tag (acrylic), Urinal bag hanger (stainless steel), Hand grip (stainless steel), Mattress (superfoam 2000 x 840 x 120 mm).
Maximum Safe Working Load	: 250 Kgs.

- Optional :**
1. Upgradeable to Hospital Bed 3 Axis Electric.
 2. Upgradeable to central lock with same direction locking system on both sides.

Standard Features :



Marketing Office :
 Jl. Sultan Iskandar Muda Kav. 24
 Jakarta Selatan 12240 - Indonesia
 P. +6221 7264150 | F. +6221 7264152

Factory & Main Logistic :
 Jl. Abdul Wahab No. 59, Cinangka,
 Sawangan, Depok - Indonesia
 P. +6221 7494512 | F. +6221 7494512
info@grahateknomedika.com
www.grahateknomedika.com